

TAPERED BUSHINGS #1215 TO 1610

BUSHING #	BORE	BUSHING KEYWAY	SHAFT KEYSEAT	A	B	D	F	WRENCH TORQUE LBS. -IN.	TORQUE CAP. LBS. -IN.	WEIGHT
1215	1/2, 9/16	1/8 x 1/16	1/8 x 1/16	1 7/8	1 1/2	1 3/4	3/8 x 5/8	175	3.550	.8
	5/8, 11/16, 3/4, 13/16, 7/8	3/16 x 3/32	3/16 x 3/32							.7
	15/16, 1, 1 1/16, 1 1/8, 1 3/16, 1 1/4	1/4 x 1/8	1/4 x 1/8							.6
1310	1/2, 9/16	1/8 x 1/16	1/8 x 1/16	2	1	1 7/8	3/8 x 5/8	175	3.850	.7
	5/8, 11/16, 3/4, 13/16, 7/8	3/16 x 3/32	3/16 x 3/32							.7
	15/16, 1, 1 1/16, 1 1/8, 1 3/16, 1 1/4	1/4 x 1/8	1/4 x 1/8							.6
	1 5/16, 1 3/8	5/16 x 5/32	5/16 x 5/32							.6
1610	1/2, 9/16	1/8 x 1/16	1/8 x 1/16	2 1/4	1	2 1/8	3/8 x 5/8	175	4.300	.9
	5/8, 11/16, 3/4, 13/16, 7/8	3/16 x 3/32	3/16 x 3/32							.8
	15/16, 1, 1 1/16, 1 1/8, 1 3/16, 1 1/4	1/4 x 1/8	1/4 x 1/8							.7
	1 5/16, 1 3/8	5/16 x 5/32	5/16 x 5/32							.7
	1 7/16, 1 1/2	3/8 x 3/16	3/8 x 3/16							.6
	1 9/16*, 1 5/8*	3/8 x 1/8	3/8 x 3/16							.5

*Denotes shallow key, keystock included. Bushings supplied with set screws made of Class 30 cast iron.



QD, TAPERED & D BUSHINGS