

TAPERED BUSHINGS #2517 TO 2525

BUSHING #	BORE	BUSHING KEYWAY	SHAFT KEYSEAT	A	B	D	F	WRENCH TORQUE LBS. -IN.	TORQUE CAP. LBS. -IN.	WEIGHT
2517	1/2, 9/16	1/8 x 1/16	1/8 x 1/16	3 3/8	1 3/4	3 1/4	1/2 x 1	430	11,600	3.5
	5/8, 11/16, 3/4, 13/16, 7/8	3/16 x 3/32	3/16 x 3/32							3.4
	15/16, 1, 1 1/16, 1 1/8, 1 3/16, 1 1/4	1/4 x 1/8	1/4 x 1/8							3.3
	1 5/16, 1 3/8	5/16 x 5/32	5/16 x 5/32							3.2
	1 7/16, 1 1/2, 1 9/16, 1 5/8, 1 11/16, 1 3/4	3/8 x 3/16	3/8 x 3/16							3.0
	1 13/16, 1 7/8, 1 15/16, 2, 2 1/16, 2 1/8, 2 3/16, 2 1/4	1/2 x 1/4	1/2 x 1/4							2.4
	2 5/16*, 2 3/8*, 2 7/16*, 2 1/2*	5/8 x 3/16	5/8 x 3/16							1.9
2525	3/4, 13/16, 7/8	3/16 x 3/32	3/16 x 3/32	3 3/8	2 1/2	3 1/4	1/2 x 1	430	11,300	4.9
	15/16, 1, 1 1/16, 1 1/8, 1 3/16, 1 1/4	1/4 x 1/8	1/4 x 1/8							4.7
	1 5/16, 1 3/8	5/16 x 5/32	5/16 x 5/32							4.5
	1 7/16, 1 1/2, 1 9/16, 1 5/8, 1 11/16, 1 3/4	3/8 x 3/16	3/8 x 3/16							4.2
	1 13/16, 1 7/8, 1 15/16, 2, 2 1/16, 2 1/8, 2 3/16, 2 1/4	1/2 x 1/4	1/2 x 1/4							3.3
	2 5/16, 2 3/8, 2 7/16, 2 1/2*	5/8 x 3/16	5/8 x 5/16							2.5

QD, TAPERED & D BUSHINGS

*Denotes shallow key, keystock included. Bushings supplied with set screws made of Class 30 cast iron.

