

TAPERED BUSHINGS #3030

BUSHING #	BORE	BUSHING KEYWAY	SHAFT KEYSEAT	A	B	D	F	WRENCH TORQUE LBS. -IN.	TORQUE CAP. LBS. -IN.	WEIGHT
3030	1 ⁵ / ₁₆ , 1, 1 ¹ / ₁₆ , 1 ¹ / ₈ , 1 ³ / ₁₆ , 1 ¹ / ₄	1/4 x 1/8	1/4 x 1/8	4 1/4	3	4	5/8 x 1 1/4	800	24,000	9.2
	1 ⁵ / ₁₆ , 1 ³ / ₈	5/16 x 5/32	5/16 x 5/32							8.9
	1 ⁷ / ₁₆ , 1 ¹ / ₂ , 1 ⁹ / ₁₆ , 1 ⁵ / ₈ , 1 ¹¹ / ₁₆ , 1 ³ / ₄	3/8 x 3/16	3/8 x 3/16							8.6
	1 ¹³ / ₁₆ , 1 ⁷ / ₈ , 1 ¹⁵ / ₁₆ , 2, 2 ¹ / ₈ , 2 ¹ / ₁₆ , 2 ³ / ₁₆ , 2 ¹ / ₄	1/2 x 1/4	1/2 x 1/4							7.6
	2 ⁵ / ₁₆ , 2 ³ / ₈ , 2 ⁷ / ₁₆ , 2 ¹ / ₂ , 2 ⁹ / ₁₆ , 2 ⁵ / ₈ , 2 ¹¹ / ₁₆ , 2 ³ / ₄ , 2 ¹³ / ₁₆	5/8 x 5/16	5/8 x 5/16							6.2
	2 ⁷ / ₈ , 2 ¹⁵ / ₁₆ , 3	3/4 x 1/4	3/4 x 3/8							5.0

*Denotes shallow key, keystock included. Bushings supplied with set screws made of Class 30 cast iron.

