

TYPE S—TAPERED WELD-ON HUBS

PART NUMBER	FOR USE WITH BUSHING	MAX BORE OF BUSHING	A	G	B	D	WEIGHT LBS.
S16-4-1610	1610	1 5/8	3.0	2 7/8	1.0	.725	.9
S16-6-1610	1610	1 5/8	3.0	2 7/8	1.0	.56	.9
S20-6-2012	2012	2	3 9/16	3 7/16	1 1/4	.8	1.8
S20-8-2012	2012	2	3 9/16	3 7/16	1 1/4	.68	1.4
S25-6-2517	2517	2 1/2	4 1/4	4.125	1 3/4	1.3	2.6
S25-8-2517	2517	2 1/2	4 1/4	4.125	1 3/4	1.185	2.6
S25-10-2517	2517	2 1/2	4 1/4	4 1/8	1 3/4	1.065	2.5
S25-16-2517	2517	2 1/2	4 1/4	4 1/8	1 3/4	.66	2.4
S30-10-3020	3020	3	5 1/4	5 1/8	2	1.325	4.3
S30-16-3020	3020	3	5 1/4	5 1/8	2	.91	4.2
S35-3535	3535	3 1/2	6 1/2	6 3/8	3 1/2	2.34	12.8

Type S Tapered Weld-On Hubs are 1035 Steel.

WELD-ON HUBS

